



SERVING AUTHORS WORLDWIDE  
AU SERVICE DES AUTEURS DANS LE MONDE  
AL SERVICIO DE LOS AUTORES EN EL MUNDO

Source language: English / Written on: 31/10/2025  
Document prepared by CISAC

## **ISWC IPI Context Search – Quick Guide for Agencies**

## 1 Introduction

The ISWC IPI Context Search allows publishers and agencies to identify an interested party (including their IPI Name Number) by searching for their name and providing work titles for additional context, as is currently possible via CIS-Net RHA. Simplified work metadata can also be provided in the results, with the user having the ability to specify the level of detail returned.

Before accessing these services in production, users will first undergo a test cycle to ensure the required specifications are being met.

This document will help to guide users through the initial test cycle for the IPI Context Search, before being onboarded to the live service after the test cycle has been completed successfully.

*NOTE: ISWCs returned during the test cycle are not genuine ISWCs and should not be disseminated*

## 2 Documentation and Sample Files

Documentation for the ISWC IPI Context Search is available to users on the ISWC Developer Portal, through the following link:

<https://cisaciswcuat.developer.azure-api.net/publisher-ipi-context-search>

## 3 Onboarding Overview

To commence UAT for the ISWC IPI Context Search, agencies should complete the following steps:

1. Log-in to the developer portal in UAT: <https://cisaciswcuat.developer.azure-api.net/>
2. Navigate to the 'APIs' page and select [ISWC Database REST API - Agency](#)
3. Locate the endpoints relating to the ISWC IPI Context Search in the list on the left of the page:

**POST** IPI context search to find IP metadata

**POST** IPI context search to find IP metadata for multiple entries simultaneously

4. Submit test API data.
5. User verifies that their software can ingest the API responses.

Once the agency has successfully performed a test per the steps above, a recommendation will be made to proceed to the Production environment <https://cisaciswcpod.developer.azure-api.net/>. The API endpoints in Production can be accessed in the same location outlined in steps 2 and 3 above.

## 4 API Performance & Throughput Guidance

### 4.1 Rate Limiting

The ISWC IPI Context Search API does not enforce a fixed rate limit.

There is also no hard limit on the number of items per batch request for the API.

However, for optimal system performance and stability, we provide the following recommendations based on internal testing.

## 4.2 Recommended Batch Size

For best performance, batch requests should contain:

10 items per request

While larger batch sizes are technically supported, performance testing has shown diminishing returns as batch size increases beyond 10 items.

Agencies are encouraged to:

- Configure their systems to send batches of 10 items.
- Adjust parallel processing levels to achieve desired throughput rather than increasing batch size.

## 4.3 Parallelism & Throughput Recommendations

Testing indicates that throughput improves significantly when using parallel requests with moderate batch sizes, rather than fewer requests containing large batches.

For example:

- 2–4 parallel threads
- Each requesting batches of 10 items

## 4.4 Implementation Best Practice

To achieve optimal performance:

- Set batch size to 10
- Use 2–3 concurrent threads as a starting point
- Increase parallelism gradually if higher throughput is required
- Avoid very large batch payloads, as these may:
  - Increase response time
  - Increase timeout risk
  - Reduce overall system efficiency

Each agency should validate optimal settings within their own infrastructure, as performance may vary depending on network configuration and system architecture.